

**PARAMETERS**

Impedance	4 ohms
Re	3.6 ohms
Le	0.02 mH @ 10 kHz
Fs	1,200 Hz
Qms	N/A
Qes	N/A
Qts	3.00
Mms	0.076 g
Cms	0.001 mm/N
Sd	N/A
Vd	N/A
BL	0.49 Tm
Vas	N/A
Xmax	N/A
VC Diameter	9 mm
SPL	N/A
RMS Power Handling	0.5 watts
Usable Frequency Range (Hz)	N/A


**FEATURES**

- Super small size; less than an inch in diameter, less than 3/8" high
- 4 ohms impedance for use with small, Class D amplifiers
- Turns almost any surface into a speaker
- Pre-applied 3M™ VHB™ adhesive for quick, secure installation
- Rare-earth neodymium motor

**APPLICATIONS**


- Invisible home theater and multi-room audio
- Electronic gaming machines
- Advertising signage
- Point-of-purchase displays
- Multimedia exhibits
- Commercial distributed audio
- Kiosks
- Automotive audio
- Bathroom tubs and showers

**IMPEDANCE/PHASE**



Measurement taken with transducer uncoupled facing upward.

**FREQUENCY RESPONSE**



OmniMic

1/3<sup>rd</sup> octave smoothing - measurement taken with transducer adhered off-center on a 12" x 12" x 1/2" foam core board in an infinite baffle setup.

Note: This information is for comparison purposes only, the actual frequency response will depend on many factors of which the diaphragm being the greatest contributor.